avide Þ

Avide LED Glass Tube 24W G13 1500mm NW 4000K High Lumen 150lm/W

Product code:	AB1500T8-24W-NW-GL-HL
Brand link:	avidelighting.com/qr/AB1500T8-24W-NW-GL-HL
ID:	AB-190518
Company name:	Bramcke Hungary Kft.
Company address:	Kishatár utca 17., 4031 Debrecen



Page: 1/3

SPECIFICATIONS

EAN code:	5999097923703
Warranty:	2year(s)
Working temperature:	-20 - +40°C
Packaging:	1/b 25/c 600/p
Certifications:	CE

PRODUCT PICTURE



TECHNICAL DETAILS	
Wattage:	24W
Voltage:	180-265V
Beam angle:	240°
Dimmability:	No
Lumen output:	3 600lm
Color temperature:	4 000K
Lifetime:	25 000h
Energy class:	A+
Type of LED:	SMD
IP standard:	IP20

avide Þ

Avide LED Glass Tube 24W G13 1500mm NW 4000K High Lumen 150lm/W

Product code:	AB1500T8-24W-NW-GL-HL
Brand link:	avidelighting.com/qr/AB1500T8-24W-NW-GL-HL
ID:	AB-190518
Company name:	Bramcke Hungary Kft.
Company address:	Kishatár utca 17., 4031 Debrecen



Page: 2/3

PRODUCT SIZE

Diameter: Length:

26mm 1 500mm

PRODUCT PICTURE



CARDBOARD BOX

EAN:	5999097923703
Packaging:	1/b 25/c 600/p
Dimensions:	35mm x 35mm x 1 575mm
Net weight:	283.5g
Gross weight:	292g

CARTON

EAN:	5999097923710
Packaging:	1/b 25/c 600/p
Dimensions:	1 590mm x 210mm x 210mm
Net weight:	7.0875kg
Gross weight:	7.3kg

PALLET EXAMPLE

Height:	
Width:	120cm (std Euro pallet)
Mepth:	80cm (std Euro pallet)
Cartons per pallet:	24carton/pallet
Cartons per row:	
Net weight:	170.1kg
Gross weight:	175.2kg

PRODUCT OUTLINE



Avide LED Glass Tube 24W G13 1500mm NW 4000K High Lumen 150lm/W

Product code:	AB1500T8-24W-NW-GL-HL
Brand link:	avidelighting.com/qr/AB1500T8-24W-NW-GL-HL
ID:	AB-190518
Company name:	Bramcke Hungary Kft.
Company address:	Kishatár utca 17., 4031 Debrecen



Page: 3/3

PRODUCT DESCRIPTION

The Avide LED dust- and moisture-proof fixtures for tubes represent the energy-saving versions of traditional fittings. The fixtures of different lengths replacing the tube fixtures have a built-in LED panel that guarantees energy-saving operation. In terms of the material used, the products have a break-resistant cover. Due to the IP65 protection of the fixture, it is protected from dust and moisture, thus can also be operated at places with higher exposure to dust and humidity.

The product range includes a 1 and 2 LED design, in lengths of 0.6, 1.2 and 1.5 meter lengths, with a transparent cover.

OUR IP protected fixture category includes numerous additional products. Learn more about these on the following link.